

Revision Date 20-May-2015

Version 1

# 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name Crystal Odor Counteractant Professional Cherry

Product code LG-F1132

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Deodorizer

Restrictions on use Professional Use Only

### 1.3 Details of the supplier of the safety data sheet

Supplier Legend Brands

ProRestore Products 15180 Josh Wilson Road Burlington, WA 98233 800-932-3030

#### 1.4 Emergency telephone number

Emergency telephone number INFOTRAC 1-800-535-5053 (North America)

1-352-323-3500 (International)

# 2. Hazards identification

# 2.1 Classification of the substance or mixture

### GHS Classification in accordance with 29 CFR 1910.1200

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A

# 2.2 Label elements

## Signal Word

Danger

## **Hazard Statements**

Causes serious eye irritation May cause an allergic skin reaction May cause cancer



# **Precautionary Statements - Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace

# **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

#### **Precautionary Statements - Storage**

Store locked up

## **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## 2.3 Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

## 2.4 Other information

Not Applicable

**Unknown Acute Toxicity** 

2.81841% of the mixture consists of ingredient(s) of unknown toxicity

# 3. Composition/Information on Ingredients

# Substance

Chemical Name	CAS-No	Weight %
BENTONITE	1302-78-9	50 - 60
AMORPHOUS SILICA	7631-86-9	10 - 20
ALUMINUM OXIDE	1344-28-1	5 - 10
IRON OXIDE	1309-37-1	1 - 5
BENZALDEHYDE	100-52-7	1 - 5
CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND	14808-60-7	1 - 5
CALCIUM OXIDE/LIME	1305-78-8	1 - 5
ISOPROPYL ALCOHOL	67-63-0	1 - 5
AMYL ACETATE	628-63-7	1 - 5
Ethyl Acetate	141-78-6	1 - 5
MAGNESIUM OXIDE	1309-48-4	< 1
TERPENES AND TERPENOIDS, SWEET ORANGE-OIL	68647-72-3	<1
Benzyl acetate	140-11-4	< 1
Titanium dioxide	13463-67-7	< 1

<sup>\*</sup> The exact percentage (concentration) of composition has been withheld as a trade secret.

# ·

# 4. First aid measures

## 4.1 Description of first-aid measures

General advice No information available.

Eye contact In case of contact with substance, immediately flush skin or eyes with running water for at

least 20 minutes. Call a poison control center or doctor for treatment advice. Tilt the head to

prevent chemical from transferring to the uncontaminated eye.

Skin contact Wash off immediately with soap and plenty of water. Remove all contaminated clothes and

shoes.

Inhalation Move to fresh air. Call a physician or poison control center immediately. If breathing is

difficult, give oxygen. If not breathing, give artificial respiration.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Dilute

with water or milk. Never give fluids if the victim is unconscious or having convulsions.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms See Section 2.2, Label Elements and/or Section 11, Toxicological effects.

#### 4.3 Recommendations for immediate medical care and/or special treatment

Notes to physician Treat symptomatically.

# 5. Fire-Fighting Measures

#### 5.1 Extinguishing media

Suitable extinguishing media

Use CO2, dry chemical, or foam. Water may be unsuitable for extinguishing fires Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Unsuitable Extinguishing Media None.

#### 5.2 Specific hazards arising from the substance or mixture

## Special Hazard

None known based on information supplied

Hazardous Combustion Products No information available.

# **Explosion Data**

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

### 5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. Thoroughly decontaminate all protective equipment after use. Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited.

# 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Dust Deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Nonsparking tools should be used.

#### Other information

Follow personal protective equipment recommendations found in Section 8. Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow the spilled product to enter public drainage systems or open waterways. Do not allow smoking in the area.

## 6.2 Environmental precautions

See Section 12 for additional Ecological information.

## 6.3 Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

# 7. Handling and storage

## 7.1 Precautions for safe handling

Advice on safe handling Routine housekeeping should be instituted to ensure that dusts do not accumulate on

surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding

and bonding, or inert atmospheres.

Hygiene measures It is good practice to avoid contact with the product and/or its vapor, mists or dust by using

appropriate protective measures. Wash thoroughly after handling and before eating or

drinking.

## 7.2 Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed. Store away from other materials. Store in a cool, dry area

away from potential sources of heat, open flames, sunlight or other chemicals.

Materials to Avoid No materials to be especially mentioned.

# 8. Exposure controls/personal protection

## 8.1 Occupational Exposure Limits (OEL)

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
BENTONITE	TWA: 1 mg/m <sup>3</sup>	-	TWA: 1.0 mg/m <sup>3</sup>			TWA: 1 mg/m <sup>3</sup>
1302-78-9	respirable fraction					
AMORPHOUS SILICA	-	TWA: 20 mppcf				
7631-86-9		: (80)/(% SiO2)				
		mg/m³ TWA		-		
ALUMINUM OXIDE	TWA: 1 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup>	TWA: 1.0 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>
1344-28-1	respirable fraction	total dust				
		TWA: 5 mg/m <sup>3</sup>				
		respirable fraction				
IRON OXIDE	TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>
1309-37-1	respirable fraction	fume	TWA: 3 mg/m <sup>3</sup>		TWA: 10 mg/m <sup>3</sup>	_
		TWA: 15 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>			
1		total dust	STEL: 10 mg/m <sup>3</sup>	}		
		TWA: 5 mg/m <sup>3</sup>				
		respirable fraction				
BENZALDEHYDE	-	-				STEL: 4 ppm
100-52-7						STEL: 17 mg/m <sup>3</sup>
CRYSTALLINE	TWA: 0.025 mg/m <sup>3</sup>	: (30)/(%SiO2 + 2)	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.10 mg/m <sup>3</sup>
SILICA (QUARTZ)/	respirable fraction	mg/m³ TWA total		_	_	-
SILICA SAND		dust				
14808-60-7		: (250)/(%SiO2 +				
		5) mppcf TWA				

		respirable fraction : (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction				
CALCIUM OXIDE/LIME 1305-78-8	TWA: 2 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m³	TWA: 2 mg/m <sup>3</sup>
ISOPROPYL ALCOHOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm TWA: 492 mg/m <sup>3</sup> STEL: 400 ppm STEL: 984 mg/m <sup>3</sup>	TWA: 400 ppm TWA: 985 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1230 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 400 ppm
AMYL ACETATE 628-63-7	STEL: 100 ppm TWA: 50 ppm	TWA: 100 ppm TWA: 525 mg/m <sup>3</sup>	TWA: 50 ppm STEL: 100 ppm	TWA: 50 ppm TWA: 266 mg/m <sup>3</sup> STEL: 100 ppm STEL: 532 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 266 mg/m <sup>3</sup> STEL: 100 ppm STEL: 532 mg/m <sup>3</sup>	TWA: 50 ppm STEL: 100 ppm
Ethyl Acetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>	TWA: 150 ppm	TWA: 400 ppm TWA: 1440 mg/m <sup>3</sup>	TWA: 400 ppm TWA: 1440 mg/m <sup>3</sup>	TWA: 400 ppm
MAGNESIUM OXIDE 1309-48-4	TWA: 10 mg/m <sup>3</sup> inhalable fraction	TWA: 15 mg/m³ fume, total particulate	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Benzyl acetate 140-11-4	TWA: 10 ppm	-	TWA: 10 ppm	TWA: 10 ppm TWA: 61 mg/m <sup>3</sup>		TWA: 10 ppm
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>

## 8.2 Appropriate engineering controls

## **Engineering Measures**

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

#### 8.3 Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Wear chemical-resistant glasses and/or goggles and a face shield when eye and face

contact is possible due to handling and processing of material.

**Skin and body protection** Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body

suit as appropriate.

Respiratory protection If irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. NIOSH/MSHA approved respiratory protection should be worn if exposure is

anticipated.

Hygiene measures See section 7 for more information

# 9. Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

Physical state Solid
Appearance crystalline
Black and Beige

**Odor** Cherry

Odor Threshold No information available

PropertyValuesRemarks • MethodspHNo information available

Melting/freezing pointNo information availableBoiling point/boiling rangeNo information availableFlash PointNo information availableEvaporation rateNo information availableFlammability (colid gas)No information available

Flammability (solid, gas)
No information available
Flammability Limits in Air

upper flammability limitNo information availablelower flammability limitNo information availableVapor pressureNo information available

Vapor pressure No information available Vapor density No information available

Specific Gravity 2.5
Water solubility No infor

Water solubilityNo information availableSolubility in other solventsNo information availablePartition coefficientNo information availableAutoignition temperatureNo information availableDecomposition temperatureNo information availableViscosity, kinematicNo information availableViscosity, dynamicNo information available

Explosive properties No information available Oxidizing Properties No information available

#### 9.2 Other information

Volatile organic compounds (VOC) 97.5 g/L content

# 10. Stability and Reactivity

# 10.1 Reactivity

No data available

## 10.2 Chemical stability

Stable under normal conditions

### 10.3 Possibility of hazardous reactions

None under normal processing.

## 10.4 Conditions to Avoid

Keep away from heat, sparks and flames.

## 10.5 Incompatible Materials

None known based on information supplied.

# 10.6 Hazardous Decomposition Products

Not determined.

# 11: Toxicological information

# 11.1 Acute toxicity

Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Unknown Acute Toxicity 2.81841% of the mixture consists of ingredient(s) of unknown toxicity

 Oral LD50
 7,356.00 mg/kg

 Dermal LD50
 10,529.00 mg/kg

Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
BENTONITE 1302-78-9	5000 mg/kg(Rat)	-	-
AMORPHOUS SILICA 7631-86-9	5000 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 2.2 mg/L (Rat) 1 h
ALUMINUM OXIDE 1344-28-1	5000 mg/kg (Rat)	-	-
IRON OXIDE 1309-37-1	10000 mg/kg(Rat)	-	-
BENZALDEHYDE 100-52-7	1292 mg/kg (Rat)	> 1250 mg/kg(Rabbit)	-
CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND 14808-60-7	500 mg/kg (Rat)	-	-
CALCIUM OXIDE/LIME 1305-78-8	500 mg/kg ( Rat )	-	-
ISOPROPYL ALCOHOL 67-63-0	1870 mg/kg (Rat)	= 4059 mg/kg(Rabbit)	= 72600 mg/m³ (Rat) 4 h
Ethyl Acetate 141-78-6	5620 mg/kg (Rat)	> 18000 mg/kg(Rabbit)	-
TERPENES AND TERPENOIDS, SWEET ORANGE-OIL 68647-72-3	4400 mg/kg(Rat)	>5 g/kg(Rabbit)	-
Benzyl acetate 140-11-4	2490 mg/kg (Rat)	> 5000 mg/kg(Rabbit)	-
Titanium dioxide 13463-67-7	10000 mg/kg(Rat)	-	-

## 11.2 Information on toxicological effects

## Skin corrosion/irritation

**Product Information** 

- · No information available
- Component Information
- No information available

## Eye damage/irritation

Product Information

- No information available
- Component Information
- · No information available

# Respiratory or skin sensitization

Product Information

- No information available
- Component Information
- · No information available

## **Germ Cell Mutagenicity**

Product Information

- No information available
- Component Information
- No information available

## Carcinogenicity

• The table below indicates whether each agency has listed any ingredient as a carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND 14808-60-7	A2	Group 1	Known	
ISOPROPYL ALCOHOL 67-63-0	-	Group 1 Group 3	-	
Titanium dioxide 13463-67-7	<del>-</del>	Group 2B	-	

# Reproductive toxicity

Product Information

- No information available Component Information
- · No information available

#### STOT - single exposure

No information available

## STOT - repeated exposure

No information available

### Other adverse effects

**Target Organs** 

- · Central nervous system
- Eyes
- Lungs
- Respiratory system
- Skin
- · Not determined.

Product Information

- No information available Component Information
- · No information available

# Aspiration hazard

Product Information

· No information available

Component Information

No information available

# 12. Ecological Information

# 12.1 Toxicity

**Ecotoxicity** 

No information available

12.43122201 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

**Ecotoxicity effects** 

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
BENTONITE	-	LC50: 96 h Oncorhynchus mykiss	

1302-78-9		19000 mg/L static	
AMORPHOUS SILICA	EC50: 72 h Pseudokirchneriella	LC50: 96 h Brachydanio rerio 5000	
7631-86-9	subcapitata 440 mg/L	mg/L static	7600 mg/L
BENZALDEHYDE	-	LC50: 96 h Oncorhynchus mykiss	-
100-52-7		10.6 - 11.8 mg/L flow-through LC50:	
		96 h Oncorhynchus mykiss 12.69	
		mg/L static LC50: 96 h Lepomis	
		macrochirus 0.8 - 1.44 mg/L	
		flow-through LC50: 96 h	
		Pimephales promelas 6.8 - 8.53	
1		mg/L flow-through LC50: 96 h	
		Lepomis macrochirus 7.5 mg/L	
		static	
CALCIUM OXIDE/LIME	-	LC50: 96 h Cyprinus carpio 1070	-
1305-78-8	1	mg/L static	
ISOPROPYL ALCOHOL	EC50: 96 h Desmodesmus	LC50: 96 h Pimephales promelas	EC50: 48 h Daphnia magna 13299
67-63-0	subspicatus 1000 mg/L EC50: 72 h	9640 mg/L flow-through LC50: 96 h	mg/L
	Desmodesmus subspicatus 1000	Pimephales promelas 11130 mg/L	, i
	mg/L	static LC50: 96 h Lepomis	
		macrochirus 1400000 μg/L	
AMYL ACETATE	-	LC50: 96 h Lepomis macrochirus	-
628-63-7		650 mg/L static	
Ethyl Acetate	-	LC50: 96 h Pimephales promelas	EC50: 48 h Daphnia magna 560
141-78-6		220 - 250 mg/L flow-through LC50:	mg/L Static
		96 h Oncorhynchus mykiss 484	<u> </u>
		mg/L flow-through LC50: 96 h	
		Oncorhynchus mykiss 352 - 500	
		mg/L semi-static	·

# 12.2 Persistence and degradability

No information available.

# 12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
BENZALDEHYDE 100-52-7	1.48
ISOPROPYL ALCOHOL 67-63-0	0.05
Ethyl Acetate 141-78-6	0.6
Benzyl acetate 140-11-4	1.96

# 12.4 Mobility in soil

No information available.

# 12.5 Other adverse effects

No information available

# 13. Disposal Considerations

# 13.1 Waste Disposal Guidance

Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.



**DOT** Not regulated

MEXNot regulatedIMDGNot regulatedIATANot regulated

# 15. Regulatory information

#### 15.1 International Inventories

TSCA Complies DSL Complies

EINECS/ELINCS ENCS IECSC -

KECL Complies PICCS -

AICS - NZIoC -

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

## 15.2 U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
ALUMINUM OXIDE	1.0
1344-28-1	
ISOPROPYL ALCOHOL	1.0
67-63-0	

### 15.3 Pesticide Information

Not applicable

## 15.4 U.S. State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND - 14808-60-7	Carcinogen
Titanium dioxide - 13463-67-7	Carcinogen
Estragole (Methyl chavicol) - 140-67-0	Carcinogen

# 16. Other information

NFPA Health Hazard 1 Flammability 0 Instability 0 Physical and chemical hazards 
HMIS Health Hazard 1 Flammability 0 Physical Hazard 0 Personal protection X

#### Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

Ceiling (C)

DOT (Department of Transportation)

EPA (Environmental Protection Agency)

IARC (International Agency for Research on Cancer)

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG)

NIOSH (National Institute for Occupational Safety and Health)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

PEL (Permissible Exposure Limit)

Reportable Quantity (RQ)

Skin designation (S\*)

STEL (Short Term Exposure Limit)

TLV® (Threshold Limit Value)

TWA (time-weighted average)

**Revision Date** 

20-May-2015

**Revision Note** 

No information available

**Disclaimer** 

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION,OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

**End of Safety Data Sheet**